### BS-104X-MRW



# BS-104X-MSW

## Wired Magnetic Sensor

### Features

- Wired magnetic sensor with a built-in Reed switch enclosed in a waterproof ABS Plastic enclosure for more safety.
- The Magnetic sensor with the high-speed reed switch ensures, the optimum sensitivity and stability.
- The sensor can be installed in all kind of cabinet, windows and doors.
- The Sensor is compatible with KNX BI Module.



General Specifications:	
Sensor Type	Magnetic Contact Switch with Built in Wires
Installation	Surface Mounted
Available Colors	White – Brown – Black
<b>Operating Distance (Gap)</b>	15~25mm
Material	ABS
N.O. Connecting Model	BS-104O-MSW
N.C. Connecting Mode	BS-104C-MSW
Model Number	BS-104X-MSW
Dimensions	33.8 x 14.2 x 6.7 mm

Technical Specification:	
Max. Switching	0.4 A
Current	
Max. Switching	110 Volt DC
Voltage	
Max. Contact	200 mΩ
resistance	
Communication	N/A - (Dry Contact
Protocol	Only)
KNX Module	Compatible
Lifetime	Up to 1,000,000 cycle
Operating temperature	-10°C ~ +60°C

#### APPLICATIONS

Door/Window Sensor Limit Switch