iBK712XX-C

KNX ROOM CONTROLLER

C SERIES | 7-inch Touch Display | iBeeSwitch



DESCRIPTION

The iBK712XX-C is a wall-mounted KNX room controller with a 7-inch touch display and integrated temperature and humidity sensors, giving one elegant point of control for the whole room.

It provides precise heating and cooling control with 2-point and proportional (continuous) thermostat functions, while its 12 programmable pages bring lighting, blinds, scenes and HVAC together on one screen.

The low-power LCD offers excellent viewing angles and an adjustable backlight for user comfort. The device is commissioned with ETS, and consists of two parts: the BCU, which handles KNX communication and auxiliary power, and the Application Board, which holds the downloaded firmware.

Main Functional Characteristics

- Switching, toggle, dimming, shutters/blinds, VRV, FCU and ventilation control, scenes, value, 2-channel and step-switching functions.
- Locking for each function and for the complete device; password protection.
- On/Off (2-point) and proportional (continuous) thermostat functions.
- Integrated temperature sensor (±0.2 °C) and humidity sensor; values are sent to the bus on change and periodically.
- The display shows measured, external, setpoint and outdoor temperature (°C or °F), humidity, operating mode, fan level, on/off status, warnings and locking status.
- Fan control with up to 3 speeds.
- Threshold alarms can be defined for temperature and humidity.
- 12 programmable pages, each with up to 8 function icons.

Models and Variations

Every model is ordered with one code. Read it from left to right:

iBK	7	12	X	X	-C
iBeeSwitch KNX	Screen size: 4 = 4" | 7 = 7" | 10 = 10"	Programmable pages: 12	Material	Color	C series


Code	Material
1	Aluminum
2	Brushed Aluminum
3	Glass
4	Plastic

Code	Color
0	Black
1	Gray
4	Gold
7	Red


Example: iBK71210-C = 7-inch screen, 12 pages, Aluminum (1), Black (0).

All rights reserved to change the model design according to the KNX Standard (2024V0.0)

Dimensions (mm)



Front view (W × H): 86 × 86 mm



Side view: 10.82 mm + 27.63 mm

Features

- **7-inch Touch Display:** clear view of lighting, curtains, environmental sensors and HVAC parameters, with responsive touch control of every function and of the room temperature.
- **Pre-programmed Scenarios:** four ready-made scenarios to set fan speed, power and other settings in one touch.
- **Versatile System Support:** works with VRV, FCU (Fan Coil Unit), heating and ventilation systems.
- **Enhanced Functionality:** also controls lighting, dimming, blinds and other KNX-compatible devices.
- **Personal Design:** the settings icon changes the background color and the page style.


Pages

- Each page holds up to 8 icons, each linked to a function: On, Off, Toggle, Step Value Switching, Setpoint Control or Operating Mode Switching.
- All thermostat functions are controlled from the touch screen.

Mounting

A. Mounting the BCU (Basic Control Unit)

Install the device on a standard round or square wall flush-mounting box, after the wall painting is complete.



1	Place the BCU in the flush-mounting box with the **"TOP"** label facing up.
2	Insert the screws through the holes marked **"1"** and **"2"**.
3	Align the BCU using the scales, then tighten the screws.

B. Mounting the Application Board onto the BCU


1	After connecting, bring the Application Board close to the BCU.
2	Hold it at a 45-degree angle and insert its top notches into the BCU's hidden mounting clips.
3	Gently press the lower notches into the slot on the side of the BCU.

All rights reserved to change the model design according to the KNX Standard (2024V0.0)

Connection to KNX Bus & Programming

The KNX bus line is connected with the black/red terminal block supplied with the device, and the auxiliary power with the yellow/white terminal block. Both blocks plug into the slots of the housing.

Press the individual address button: the red programming LED turns on and the device is ready for programming.



1	KNX Bus (black/red terminal block)
2	Auxiliary Power 12–30 VDC (yellow/white terminal block)
3	Individual Address Button

Safety Instructions

- The device should only be installed and put into operation by a qualified electrician or authorized person.
- Do not connect mains voltage (230 VAC) or any other external voltage to any point of the KNX bus.
- Install only in dry indoor locations, in a wall flush-mounting box. Do not expose the device to direct sunlight, rain or high humidity.
- Ensure adequate insulation and separation between 230 VAC cables and the KNX bus.
- Do not use aerosol sprays, solvents or abrasives.

Technical Data

Electrical Parameters	Specification
Device Name	iBK712XX-C
Display	7-inch touch LCD
Programmable Pages	12
Power Supply	KNX bus voltage + auxiliary power
Bus Current Consumption	< 12 mA
Auxiliary Voltage	12–30 VDC
Auxiliary Power Consumption	< 5 W
Programming	Button to assign the physical address; red LED on while in programming mode

Environmental Parameters

Parameter	Specification
Operating Humidity	< 90% RH
Storage Humidity	Up to 90%
Operating Temperature	-10 °C to +45 °C
Storage Temperature	-15 °C to +55 °C
Transport Temperature	-15 °C to +70 °C
Sensors	Temperature sensor (±0.2 °C) Humidity sensor

All rights reserved to change the model design according to the KNX Standard (2024V0.0)

Device Parameters

Parameter	Specification
Protection Type	IP20
Mode of Communication	S-Mode
Mounting	Wall flush-mounting box (round or square)
Flammability	Non-flammable product
Dimensions (W × H × D)	86 × 86 × 10.82 mm
KNX Bus Connector	0.6–0.8 mm Ø, solid
Connectors	Screw terminal, 2.5 mm² stranded to 4 mm² solid
Tightening Torque	Maximum 0.5 Nm
Available Colors	Gold, Red, Black & Gray
Password Protection	Available
Warranty Period	18 months

EU Main Office:

Vitosha,JK.Manastrski Livadi
5A Maistor Dimitar Sofianliata Str.
Sofia, Bulgaria.

All rights reserved to change the model design according to the KNX Standard (2024V0.0)